



AT A GLANCE

Nano Technology
Environmental friendly
VOC and APEO free


Water vapor permeable
Reduces surface abrasion
Indoor and outdoor use



Description

Pro Oil 2K strengthens the seal of ProEco 330 or ProEco Plus. Pro Oil 2K gives resistance and additional protection and enhances the color on Seamless Terrazzo, Seamless Flow and Trowel. Pro Oil 2K is a newest generation product which color enhance overlay and protects it in one layer. The combination of the oil (A) and the accelerator (B) guarantees a quick drying. It can also be applied as renovation and maintenance oil on surfaces which are treated with ProEco 330 or ProEco Plus. Applied in only one layer. It can be pigmented to enhance white or dark colors.

- Enhances the natural look and feel of overlay or terrazzo
- Environmental friendly: 0% VOC!
- Does not contain any water or solvents
- Easy to maintain
- No overlaps or starting marks
- Durable protection
- Minimal use: 60 - 120 m²/L
- Wear-resistant
- Water-resistant, ideal for kitchens and bathrooms
- Heat-resistant
- Very fast curing: 80% in 2 days
- After 5 days, the surface can be cleaned with water and soap



TECHNICAL PROPERTIES AND CHARACTERISTICS

Physical state at 20°C	Liquid
Odour	A Component: Oily B Component: None
Flash Point	A Component: 99°C B Component: 160 ° C
Density	B Component 0.90 g/cm ³
VOC Content	0 g/l
Application temperature	Min. +5 °C, max. +55 °C
Consumption	60-120 m ² /L in 1 application

Application information

Pro Oil 2K is applied as a top sealer on ProEco 330 and ProEco Plus when surface preparation is done. If the surface has become dirty or dusty, it should be cleaned with a scrubber drier and left to dry. Carefully mix the two components (1 to 2 minutes).

Once the cleaned surface is dry, spread out a small quantity of Pro Oil 2K (cloth or polishing machine with thin white pad). Work in zones of 5 - 10 m². Let absorb during a few minutes. Thoroughly remove all excess of oil (cloth or polishing machine with white pad) within 15 minutes per zone. The surface should feel dry! Finish all zones the same way. In a well ventilated room, the surface can be used 24 - 36 hours after the application. After 5 days the floors can be washed with PH neutral soaps.

› Tips & tricks

- The product must NOT be diluted!
- Stir the product well before application. When using several containers at one site, it is recommended to mix them for an even result.



etonsurfaces
inspiring technology

PRODUCT DATA SHEET

Pro Oil 2K

Versatile Sealer

October 2020

ATTENTION

Cloths saturated with oil may spontaneously combust. After usage, they need to be soaked in water before disposal.

Consumption

60 - 120 m²/L, depending on the floor finish. Pro Oil 2K may be used for a maximum of 4 - 6 hours after mixing. It is always recommended to make a sample in order to calculate the exact usage.

Production, packaging, storage, safety and validity

Combined can of 1,3 L: 1 L Pro Oil 2K (A) and 0,3 L Pro Oil 2K Accelerator (B)

Combined can of 3,5 L: 2,750 L Pro Oil 2K (A) and 0,750 L Pro Oil 2K Accelerator (B)

The product can be stored up to 36 months in dry conditions and in its original packaging. Keep away from frost and store at stable temperatures.

Safety and Health

Use adequate PPE: waterproof gloves boots and goggles.

Avoid contact with skin and eyes; prolonged contact may cause skin irritation.

Do not drink, eat or smoke while handling the product.

Non flammable and non-explosive product.

See the complete product MSDS.

LIMITED WARRANTY

Etonsurfaces Inc. warrants its materials to be of good quality and, at its option, will replace or refund the purchase price of any material proven to be defective within one (1) year from date of purchase. The above remedies shall be the limit of Etonsurfaces Inc.'s responsibility. Except for the foregoing, all warranties expressed or implied, including merchantability and fitness for a particular purpose, are excluded. Etonsurfaces Inc. shall not be liable for any consequential, incidental, or special damages arising directly or indirectly from the use of the materials.